



Full-function Island Drive-up ATM

This is a full-function drive-up ATM in an island fashion. This unit is self-contained and secure for the demands of drive-up banking. Featured modular design, it is an ease of service and maintaining. With options of bundle cash and check deposit, the ATM can be considered as an automated branch in the drive-up lane, offering compelling solutions to extend banking channel.



Full-function Island Drive-up ATM

SPECIFICATIONS

Industrial PC

- ◆ Pentium 4 3.0GHz or higher CPU, 1G or more RAM, 160GB or higher HDD, DVD-RW

Display

- ◆ 15" TFT color LCD with 2x4 function display keypads
- ◆ 15" TFT color LCD with touch screen (optional)
- ◆ Privacy display filter (optional)
- ◆ Sunlight viewable TFT LCD (optional)
- ◆ Digitized voice guidance

Keypad

- ◆ Tactile 4 X 4 numeric metal keypad with English keys of "ENTER", "CLEAR", "CANCEL", local language keys are optional
- ◆ 2x4 function display keys
- ◆ PCI EPP
- ◆ Vandal resistant & dust proof
- ◆ Beep responding on key press

Lead-Through Indicator

- ◆ Card reader indicator
- ◆ Receipt printer indicator
- ◆ Cash input/output indicators
- ◆ Envelope deposit indicator (optional)

Operator Interface

- ◆ ATM Status Indicator
- ◆ LCD service panel with 10.4" touch screen
- ◆ User-friendly Maintenance Manager
- ◆ Privilege management with supervisor menu
- ◆ Self-diagnosis & error inquiring
- ◆ E-journal output to DVD-RW

Card Reader

- ◆ Motorized card reader/writer (magnetic/smart card, Hi-Co track 1/2/3 read and write, EMV certified.)
- ◆ Card capture capability
- ◆ Anti-fishing/skimming security features (optional)
- ◆ Card return on power failure (optional)
- ◆ DIP card reader/writer (optional)

Printer

- ◆ Graphic Receipt Printer
 - High-speed graphics thermal printer
 - Local character printing
 - Receipt retract function in case it is not taken
- ◆ Mini statement printing (optional)
- ◆ Journal Printer
 - Dot matrix or thermal printer
- ◆ USB 2.0 Communication

Envelope Deposit Unit (Optional)

- ◆ Motorized envelope feeding
- ◆ Integrated dot matrix printer
- ◆ Envelope capacity: Max. 100 bank notes per envelope
- ◆ Envelope depository bin capacity:
 - Approximate 200 envelopes with 15 notes per envelope

Cash Acceptor(Optional)

- ◆ Accepts and validates up to 100 notes per transaction
- ◆ Storage up to 3000 notes
- ◆ Accepting speed: 6 notes per second

Check Processor (Optional)

- ◆ True MICR read of E13B or CMC7 code line
- ◆ Front and Rear imaging of documents
- ◆ Inkjet rear side endorsement
- ◆ Double feed detection and document alignment in paper path
- ◆ USB2.0 communication

Dispenser

- ◆ High-speed dispenser
 - Frictional bundle-cash dispensing
 - Dispensing speed: 7 notes per second
 - Maximum 60 notes per bundle
 - Note Cassette: standard 2, maximum 4
 - 1 Reject Vault, separately retract and divert compartment
 - Note Cassette capacity: inner length 350 mm (13.8 in.), approximately 3000 new notes
 - Universal media size range support
 - Reject Vault capacity: Max. 250 notes (bundle reject) + 100 notes (single reject)

Security

- ◆ Physical:
 - UL291 standard Level 1 safe
 - Electronic combination lock
 - Mechanical combination lock (optional)
- ◆ PCI EPP
- ◆ EMV certified
- ◆ DVR surveillance system (optional): Video capture triggered by time, alarm, transaction or motion detecting
- ◆ Transaction image capture for surveillance (optional)

Software

- ◆ Operating system: Windows XP Pro
- ◆ ATM Application Software
 - NDC/NDC+ emulation
 - DDC emulation:
 - ISO8583 emulation
 - Standard CEN/XFS SP
- ◆ Can be customized to comply with any ATM switching system

Network Communication

- ◆ Standard TCP/IP, leased line connection
- ◆ PSTN dial-up connection (optional)
- ◆ Wireless connection (optional): GPRS/CDMA
- ◆ SNA/SDLC (optional)
- ◆ X.25 (optional)

Working Environment

- ◆ Operating temperature:
 - 32°F (0°C) to 122°F (50°C)
 - 31°F (-35°C) to 122°F (50°C) with thermostat unit
- ◆ Relative humidity: 20% to 95% non-condensing
- ◆ Thermostat Unit (optional)

Power Consumption

- ◆ AC110-120V~/220-240V~, 50-60Hz
- ◆ Idle: 165W
- ◆ Working: 240W
- ◆ UPS (optional)
 - 1KVA
 - Intelligent emergency power supply and power cut off alarm

Dimensions & Weight

- ◆ Height: 55.4 in. (1408 mm)
- ◆ Width: 45.3 in. (1150 mm)
- ◆ Depth: 35.8 in. (910 mm)
- ◆ Weight: 2205lbs (1000 kg)

Talk to us

We want to provide you with a personal service rather than a computer-generated response. Please enter your details below so one of our sales representatives can get in touch within 24 hours on week days.

Or if you prefer, contact us instead on 1300 915 665 or team@ylatm.com.au.